

**REQUIRED EQUIPMENT LIST**

SERIAL NO. \_\_\_\_\_ REG. NO. \_\_\_\_\_ PROD. NO. \_\_\_\_\_

NOTE: Equipment items installed below are designated by check marks.

CATEGORY, MANUFACTURER AND PART OR MODEL NO. \_\_\_\_\_ WEIGHT (Lbs) \_\_\_\_\_ ARM (Ins) \_\_\_\_\_

**PROPELLER AND ACCESSORIES**

**1. PROPELLER**

A. Hartzell

1.	HC-C2YR-1BF/F7666A	(M4180V/M5/6/MX7/MXT7180/MX7180B/C)	56.0	-61.3
2.	HC-C2YR-1BF/F8468A-6R	(M5/6/8/MX7/MT7235/M7235/A/B/C)	50.0	-61.5
3.	HC-C2YR-1BF/F8468A-3R	(M5/6/8/MX7/MT7235/M7235/A/B/C)	51.0	-61.5
4.	HC-C2YR-1BF/F8477D-6*	(M5/6/8/MX7235/M7235/A/B/C/260/C/MT7260)	50.0	-61.5
5.	HC-C3YR-1RF/F7693(F)-( )**	(M5/6/8/MX7235/M7235/A/B/C/MT7235/260/M7260/C)	73.0	-61.5

(-3R with 7:00 min. tires/26 psi min.) (\*For -235, use with O-540-J3A5/B4B5 engines only)

(\*\*For -235, not approved with O-540-J1A5D engine)

B. McCauley

1.	B3D32C414-[ ]/[ ]-82NDA-4	(M5/6/8/MX7/MT7235/M7235/A/B/C/260/C/MT7260)	66.5	-61.5
2.	B3D32C414-[ ]/[ ]-82NDA-2	(M5/6/8/MX7/MT7235/M7235/A/B/C/260/C/MT7260)	67.0	-61.5
3.	B2D37C224-B/G-90RA-9*	(M5/6/8/MX7/MT7235/M7235/A/B/C)	48.5	-61.5
4.	B2D37C224-[ ]/[ ]-90RA-12	(MT7260/M7260/C)	48.5	-61.5
5.	B2D37C224-[ ]/[ ]-90RA-10.5	(MT7260/M7260/C)	48.5	-61.5

(-9 with 7:00 min. tires/26 psi min.; \* foreign use only with -260)

C. Sensenich

1.	74DM7S5-0-52	(MXT7/MX7-160/160C only)	36.3	-60.5
2.	74DM7S5-0-54	(MXT7/MX7-160/160C only)	36.3	-60.5
3.	74DM7S5-0-56	(MXT7/MX7-160/160C only)	36.3	-60.5
4.	74DM7S8-0-52	(MXT7/MX7-160/160C only)	36.3	-60.5
5.	74DM7S8-0-54	(MXT7/MX7-160/160C only)	36.3	-60.5
6.	74DM7S8-0-56	(MXT7/MX7-160/160C only)	36.3	-60.5
7.	76EM8S5-0-56	(M4-180V/MXT7-180A/MX7-180A/AC only)	36.4	-60.5
8.	76EM8S8-0-56	(M4-180V/MXT7-180A/MX7-180A/AC only)	36.4	-60.5

D. MT

1.	MTV-14-B/190-17	(MT7260/M7260/C)	49.2	-61.5
----	-----------------	------------------	------	-------

**2. SPINNER & BULKHEAD ASSEMBLY**

A. Hartzell

1.	A2298-2	(Use with propeller A.1,2,3,4 only)	4.0	-62.2
2.	82C-3535-1P	(Use with propeller A.5 only)	5.0	-62.2

B. McCauley

1.	D-6240	(Use with propeller B.1,2 only)	4.2	-62.3
2.	D-6195	(Use with propeller B.3,4,5 only)	5.5	-62.3

C. Sensenich

1.	S74DM	(Use with propeller C.1-6 only)	4.8	-61.5
2.	S76EM	(Use with propeller C.7,8 only)	4.6	-61.5

D. MT

1.	P-238-A-1	(Use with propeller D.1 only)	3.8	-61.5
----	-----------	-------------------------------	-----	-------

**3. GOVERNOR (Not used with Fixed Pitch Propellers)**

A. Woodward

1.	H210681	(O-360 only)	4.5	-52.5
2.	B210761	(O-540-J/IO-540-W only)	4.5	-52.5

**REQUIRED EQUIPMENT LIST**

SERIAL NO. \_\_\_\_\_ REG. NO. \_\_\_\_\_ PROD. NO. \_\_\_\_\_

NOTE: Equipment items installed below are designated by check marks.

CATEGORY, MANUFACTURER AND PART OR MODEL NO. WEIGHT (Lbs)    ARM (Ins)

3.	F210681*	(O-540-J/IO-540-W only)	4.5	-52.5
4.	E210761	(O-540-B only)	4.5	-52.5

(\*Refer to AD #81-25-01 for eligibility information.)

**B. McCauley**

1.	C290D3(X)/T30	(O-540-J/IO-540-W only)	2.8	-52.5
2.	C290D3(X)/T31	(O-540-B only)	2.8	-52.5
3.	C290D3(X)/T29	(O-360 only)	2.8	-52.5
4.	DC290D1(X)/T14	(O-540-J/IO-540-W only)	2.8	-52.5
5.	DC290D1(X)/T15	(O-540-B only)	2.8	-52.5
6.	DC290D1(X)/T12	(O-360 only)	2.8	-52.5
7.	DC290D1(X)/T33	(IO-540-V only)	2.8	-52.5

**ENGINE AND ACCESSORIES**

**4. ENGINE**

**A. Textron/Lycoming**

1.	O-360-C1F*	(M4-180V/M5/6/MX7/MXT7-180/MX7/MXT7-180A/MX7-180B/C/AC)	288.2	-42.2
2.	O-540-J1A5D	(M5/6/8/MX7-235/M7-235/A/B/C)	390.1	-39.6
3.	IO-540-W1A5D	(M5/6/8/MX7/MT7-235/M7-235/A/B/C)	395.5	-39.6
4.	O-540-B4B5	(M5/6/8/MX7-235/M7-235/A/B/C)	395.6	-39.5
5.	O-320-B2D	(MX7-160/C/MXT7-160 only)	282.5	-42.2
6.	O-540-J3A5	(M5 6/8/MX7-235/M7-235/A/B/C)	395.2	-39.6
7.	IO-540-W1A5	(M5/6/8/MX7/MT7-235/M7-235/A/B/C)	394.0	-39.6
8.	O-360-C4F	(M4-180V/MX7/MXT7-180A/MX7-180AC)	293.0	-42.2
9.	IO-540-V4A5	(MT7-260/M7-260/C)	402.5	-39.6

(\*Requires modification when used with fixed pitch propeller)

**5. OIL COOLER**

**A. Harrison**

1.	8529245	(O-320/O-360/IO-540 only)	3.5	-26.0/-25.0
2.	8534108	(O-540-J only)	3.5	-45.0

**B. Niagara**

1.	20003A	(O-360/O-320 only)	3.5	-26.0
2.	20006A, 20003A	(O-540 only)	3.5	-45.0
3.	20003A	(IO-540 -235 only)	3.5	-25.0
4.	20006A	(IO-540 -260 only)	3.5	-25.0

**ELECTRICAL**

**6. BATTERY**

**A. Exide**

1.	AC78M	(12 volt)	27.0	**
----	-------	-----------	------	----

**B. Rebat**

1.	R-35M	(12 volt)	26.4	**
----	-------	-----------	------	----

**C. Willard**

1.	W-78M	(12 Volt)	27.0	**
----	-------	-----------	------	----

**REQUIRED EQUIPMENT LIST**

SERIAL NO. \_\_\_\_\_ REG. NO. \_\_\_\_\_ PROD. NO. \_\_\_\_\_

NOTE: Equipment items installed below are designated by check marks.

CATEGORY, MANUFACTURER AND PART OR MODEL NO. WEIGHT (Lbs) ARM (Ins)

**D. Concorde**

1.	CB 35M	(12 volt)	26.5	**
2.	RG-35A	(12 volt)	29.5	**
3.	RG-35AXC	(12 volt)	32.0	**

**E. Teledyne/Gil**

1.	G-35M	(12 volt)	27.0	**
2.	G-243	(24 volt)	28.0	***
3.	G-35S	(12 volt)	27.0	**

\*\* Battery Arm: -19.5" for MX7-160/C/180A/B/C/AC/MXT7-160/180/A; 13" for M4-180V/M5/6/MX7-180; 95" (lt. side) or 112" (rt. side) for M7/MT7; 96" (lt. side) or 108" (rt. side) for M5/6/8/MX7-235. Note: M7 s/n's 4001C-4016C. 4019C and 4020C, battery installed at 13" arm.

\*\*\* Battery Arm: 14" for M4-180V/M6-180/MX7-160/C/180/A/B/C/AC/MXT7-160/180/A; 96.4" (lt. side) or 95.6" (rt. side); for M7/MT7; 101.1" for M6/M8/MX7-235.

**7. BATTERY SOLENOID**

**A. White Rodgers/RBM/Essex**

1.	71-111221-5	(14 volt)	(M4-180V/M5/6/MX7-180)	.9	12.5
			(MX7-160/C/180A/B/C/AC/MXT7-160/180/A)	.9	-18.0
			(M7/MT7, lt. side)	.9	80.0
			(M7/MT7, rt. side)	.9	106.5
			(M5/6/8/MX7-235)	.9	101.5
2.	71-117226-5	(28 volt)	(M4-180V/MX7-160/C/180A/B/C/AC/MXT7-160/180/A)	.8	12.5
			(M7/MT7, lt. side)	.9	80.0
			(M7/MT7, rt. side)	.8	106.5
			(M8/MX7-235)	.8	101.5

**8. STARTER SOLENOID**

**A. Prestolite**

1.	SAZ-4201E		.7	-18.0
----	-----------	--	----	-------

**B. White Rodgers/RBM Controls/Essex**

1.	70-112225-5	(14 volt)	.7	-18.0
2.	70-118225-5	(28 volt)	.7	-18.0

**9. ELECTRICAL FUEL PUMP**

**A. Dukes Astronautics**

1.	1184-00-1	(O-320/-360/-540 only)	(14 volt)	2.1	-20.0
2.	1184-00-3	(O-320/-360/-540 only)	(14 volt)	2.1	-20.0
3.	1471-00-1	(IO-540 only)	(14 volt)	2.1	-20.0
4.	1471-00-3	(IO-540 only)	(14 volt)	2.1	-20.0
5.	4140-00-400	(O-320/-360/-540)	(28 volt)	2.1	-20.0
6.	4140-00-401	(IO-540)	(28 volt)	2.2	-20.0

**10. ALTERNATOR CONTROL \*\* (See next page)**

**A. Precision Airmotive Corporation/Lamar, Inc.**

1.	B-00371-8	(14 volt)	.3	-16.0
2.	B-00368-12	(28 volt)	.3	-16.0

**B. Electrosystems**

1.	VR371	(14 volt)	.3	-16.0
----	-------	-----------	----	-------

**REQUIRED EQUIPMENT LIST**

SERIAL NO. \_\_\_\_\_ REG. NO. \_\_\_\_\_ PROD. NO. \_\_\_\_\_

NOTE: Equipment items installed below are designated by check marks.

CATEGORY, MANUFACTURER AND PART OR MODEL NO.	WEIGHT (Lbs)	ARM (Ins)
--	--------------	-----------

\*\* For Alternator Control System prior to Precision Airmotive (Lamar) Alternator Control System: Voltage Regulator p/n VSF-7203(S) (Prestolite); Over-Voltage Relay p/n FOC-4002A (Prestolite).

**11. PANEL LIGHT DIMMER**

A. Precision Airmotive Corporation/Lamar, Inc.

1. B-00396-1/-2 (14/28 volt)	.3	-16.0
------------------------------	----	-------

**INSTRUMENTS**

NOTE: REQUIRED INSTRUMENT MARKINGS TO BE PER AFM/AFMS.

**12. STALL WARNING**

A. Maule

1. 6016F	.1	1.5
----------	----	-----

**13. COMPASS**

A. Hamilton Instruments

1. HI-400	.6	-2.0
-----------	----	------

B. Airpath

1. C-2300	.8	-2.0
2. C-2300-DL	.8	-2.0
3. C-2400-LP	.8	-2.0
4. C-2400-L4P	.8	-2.0

**14. ALTIMETER**

A. Kollsman

1. C-12	1.0	-2.0
2. C-13	1.0	-2.0
3. B-11	1.0	-2.0

B. Aerosonic

1. 101720-01545	1.0	-2.0
2. 101720-01546 (Mb)	1.0	-2.0
3. 12003	1.0	-2.0
4. 101720-01694	1.0	-2.0

C. Aeritalia

1. 16030SK	1.2	-2.0
------------	-----	------

D. United Instrument/Mitchell

1. 5934-1 code A68 (InHg)	1.0	-2.0
2. 5934P-1 code A83 (InHg w/Barber pole)	1.0	-2.0
3. 5934PM 1 code A84 (Mb w/Barber pole)	1.0	-2.0
4. 5934D-1 code A129 (Dual-Mb/InHg)	1.0	-2.0
5. 5934PD-1 code A130 Dual-Mb/InHg w/Barber pole)	1.0	-2.0
6. 5934M-3 code A73 (Mb)	1.0	-2.0
7. 5934P-3 code A83 (InHg w/Barber pole)	1.0	-2.0

E. Reporting Altimeters per Section 5.C of Optional Equipment List.

**15. AIRSPEED**

A. Aerosonic

1. 230-217-56-1210	.8	-2.0
2. 230-220-56-1210	.8	-2.0

**REQUIRED EQUIPMENT LIST**

SERIAL NO. \_\_\_\_\_ REG. NO. \_\_\_\_\_ PROD. NO. \_\_\_\_\_

NOTE: Equipment items installed below are designated by check marks.

CATEGORY, MANUFACTURER AND PART OR MODEL NO. WEIGHT (Lbs) ARM (Ins)

3.	230-40-201-2	.8	-2.0
4.	230-217-56-1410	.8	-2.0
5.	S15KAW	1.0	-2.0
6.	20025-01200	.8	-2.0
7.	20025-01208	.8	-2.0
8.	S18KAW-1	.8	-2.0

**B. EDO-Aire/Sigma Tek, Inc.**

1.	EA5171-01 MAL (MPH/KNOTS)	.7	-1.0
2.	EA5171-02 MAL (MPH/KNOTS)	.6	-1.0
3.	EA5171-03 MAL (TAS)	.6	-1.0
4.	EA5171-04 MAL (TAS)	.6	-1.0
5.	EA5171-05 MAL (TAS)	.6	-1.0
6.	EA5171-06 MAL (MX7-180/A/B/C,MXT7-180A) (KNOTS)	.6	-1.0
7.	EA5171-07 MAL (M6/MX7-235, M8-235) (KNOTS)	.6	-1.0
8.	EA5171-08 MAL (M-7-235) (KNOTS)	.6	-1.0
9.	EA5171-09 MAL (M4-180V,MXT7-180,M7-235A/B/C/260/C/MT7-235/260) (MPH/KNOTS)	.6	-1.0
10.	EA5171-010 MAL (M4-180V,MXT7-180,M7-235A/B/C/260/C/MT7-235/260) (KNOTS)	.6	-1.0
11.	EA5174-01 PT-MAL (TAS)	.6	-1.0
12.	EA5174-02-PT-MAL (TAS)	.7	-1.0
13.	EA5174-03 PT-MAL (M6/MX7/M8-235) (TAS)	.7	-1.0
14.	EA5174-04 PTL-MAL (MX7-180/A/B/C,MXT7-180A) (TAS)	.7	-1.0
15.	EA5174-05 PTL-MAL (M7-235) (TAS)	.7	-1.0
16.	EA5174-06 PTL-MAL (M4-180V,MXT7-180,M7-235A/B/C/260/C/MT7-235/260) (TAS)	.7	-1.0

**C. United Instruments, Inc.**

1.	UI8000-B690 (MX7-160/C,MXT7-160) (MPH/KNOTS)	.7	-1.1
2.	UI8000-B844 (MX7-160/C,MXT7-160) (KNOTS)	.7	-1.1

**16. INSTRUMENT CLUSTER**

**A. MAULE**

1.	7040B	1.0	-0.6
----	-------	-----	------

**17. MANIFOLD PRESSURE/FUEL PRESSURE (O-360/O-540 only)**

**A. Aeronomic**

1.	735-102	1.0	-1.5
----	---------	-----	------

**B. EDO-Aire/Sigma Tek**

1.	IU028-005-38	1.0	-1.0
----	--------------	-----	------

**C. Castleberry Instruments & Avionics, Inc.**

1.	6331 H 14	1.0	-1.0
----	-----------	-----	------

**D. United Instrument, Inc.**

1.	UI6333-H.170	1.0	-1.0
----	--------------	-----	------

**18. FUEL PRESSURE GAUGE (O-320/O-360 w/fixed pitch only)**

**A. United Instruments**

1.	6213	.5	-1.0
----	------	----	------

**19. MANIFOLD PRESSURE/FUEL FLOW (IO-540 only)**

**A. A.I.D.**

1.	21-1003-1	1.0	-1.5
----	-----------	-----	------

**REQUIRED EQUIPMENT LIST**

SERIAL NO. \_\_\_\_\_ REG. NO. \_\_\_\_\_ PROD. NO. \_\_\_\_\_

NOTE: Equipment items installed below are designated by check marks.

CATEGORY, MANUFACTURER AND PART OR MODEL NO. WEIGHT (Lbs)    ARM (Ins)

B. United Instruments, Inc.

1.	UI6333-H.151	1.0	-1.5
----	--------------	-----	------

C. Sigma-Tek

1.	1U028-005-65	1.3	-1.5
----	--------------	-----	------

**20. TACHOMETER**

A. Stewart-Warner

1.	551-AWB (O-360/O-320 only)	.8	-1.1
2.	551-ACR	.8	-1.1
3.	551-ASJ	.8	-1.1

B. AC

1.	RT-7	.8	-1.1
2.	AC6412611	.8	-1.1

C. Aerosonic

1.	70-108	.8	-1.1
----	--------	----	------

D. Mitchell

1.	98480-23 (O-540/IO-540 only)	.8	-1.1
2.	98480-24 (O-360/O-320 only)	.8	-1.1
3.	CD-122-5005 (O-320-B2D, O-360-C4F (Fixed Pitch), IO-540-V4A5)	.8	-1.1
4.	D1-112-5024 (O-360-C1F - Fixed Pitch)	.8	-1.1
5.	CD-122-5004 (O-360-C1F - Constant Speed)	.8	-1.1
6.	CD-122-5006 (O-540-J1A5D/J3A5, IO-540-W1A5D/W1A5)	.8	-1.1
7.	CD-122-5008 (O-540-B4B5)	.8	-1.1

E. Electronic International

1.	R-1-4-G30R270 (O-320-B2D, O-360-C4F)	.6	-1.8
2.	R-1-4-G30R215G235R270 (O-360-C1F - Fixed Pitch)	.6	-1.8
3.	R-1-4-G30R200G225R270 (O-360-C1F - Constant Speed)	.6	-1.8
4.	R-1-6-G30R240 (O-540-J1A5D/J3A5)	.6	-1.8
5.	R-1-6-G30R240 (IO-540-W1A5D/W1A5)	.6	-1.8
6.	R-1-6-G30R257 (O-540-B4B5)	.6	-1.8
7.	R-1-6-G30R270 (IO-540-V4A5)	.6	-1.8

**LANDING GEAR**

**21. TIRES w/TUBES (2 ea.) TYPE III 4/6 PLY TO TSO C62b**

A.	6:00 x 6 (Nosewheel - 1 each)	8.3	-41.0
B.	7:00 x 6 (For Trigear Mains)	16.6	30.4
C.	7:00 x 6 (For Tailwheel Models)	23.6	*
D.	8:00 x 6 (For Tailwheel Models only)	25.2	*
E.	8:50 x 6 (For Tailwheel Models only)	38.2	*

\*-2.5 for Oleo Gear, -1.0 for Spring Gear

**22. MAIN WHEEL (2 ea.)**

A. Cleveland

1.	40-97D	12.4	*
2.	40-75D (Dual) (For-Tailwheel Models only)	12.8	*
3.	40-28	10.2	*
4.	C38500HA	10.2	*

**REQUIRED EQUIPMENT LIST**

SERIAL NO. \_\_\_\_\_ REG. NO. \_\_\_\_\_ PROD. NO. \_\_\_\_\_

NOTE: Equipment items installed below are designated by check marks.

CATEGORY, MANUFACTURER AND PART OR MODEL NO. WEIGHT (Lbs) ARM (Ins)

**23. BRAKES - MAIN WHEEL (2 ea.)**

A. Cleveland

1.	30-63E	3.8	*
2.	30-52N (Dual)	5.8	*
3.	30-18	3.0	*
4.	C2000	3.6	*
5.	30-52K (Dual)	5.8	*

\*-2.5 for Oleo Gear, -1.0 for Spring Gear

**24. TAILWHEEL (Tailwheel Models only)**

A. MAULE

1.	SFS-P8A-1-2	7.0	185.0
2.	SFS-P8B-1-2	8.0	185.0

B. Alaskan Bushwheel (ABI-4000 Leaf Springs may be used in lieu of Maule Leaf Springs 4004E, 4005E & 4006E)

1.	ABI-3200	8.0	185.8
2.	ABI-3224A	8.2	185.8

**SAFETY BELTS**

**25. FRONT SEAT BELT & SHOULDER HARNESS ASSEMBLIES (2 ea.)**

A. AM-Safe, Inc.

1.	500661-401	2.6	36.0
2.	500661-405	2.6	36.0
3.	500661-413	2.6	36.0
4.	502338-413 (R) /-417 (L) (Rotary Buckle)	2.6	37.0
5.	502338-423 (R) /-425 (L) (Rotary Buckle)	2.5	37.0
6.	3102-1-011-2396 (3-Point Shoulder Harness & Lap Belt)	2.5	37.0
7.	4098-1-021-2396 (4-Point Shoulder Harness & Lap Belt)	2.5	37.0

B. Pacific Scientific (Rotary Buckle)

1.	1101020-7 (L)/-9 (R) (Lap Belt)	1.6	36.0
2.	2B25A( )X-15 (Shoulder Harness)	.9	38.0

C. Davis

1.	FDC-6400-568-2/4	2.6	36.0
2.	FDC-8300-64R-080		36.0
3.	FDC-8300-64L-080		36.0

**26. REAR SEAT BELT (1 ea.) & SHOULDER HARNESS/LAP BELT ASSEMBLIES (2 ea.)**

A. Rupert

1.	Series MM 65-80 AC (Lap Belt - Double Occupant)	.6	52.0
----	---	----	------

B. AM-Safe, Inc.

1.	500915-3 (Lap Belt - Double Occupant)	.6	52.0
2.	500661-409 (Shoulder Harness & Lap Belt)	2.5	55.0/80.0
3.	3102-1-071-2396 (3-Point Shoulder Harness & Lap Belt)	2.5	55.0/80.0

C. Davis

1.	FDC-6400-568-1/3	2.6	55.0/80.0
----	------------------	-----	-----------

**REQUIRED EQUIPMENT LIST**

SERIAL NO. \_\_\_\_\_ REG. NO. \_\_\_\_\_ PROD. NO. \_\_\_\_\_

NOTE: Equipment items installed below are designated by check marks.

CATEGORY, MANUFACTURER AND PART OR MODEL NO. WEIGHT (Lbs)    ARM (Ins)

**27. CARGO & LUGGAGE STRAPS**

A. Kine-Dyne

1.	3101003GO72-022 (Front)	.8	43.5
2.	3101003GO72-022 (Rear)	.8	71.0

B. DOT Tiedown and Lifting Equipment

1.	C506SE (M-4-180V)	1.2	43.5
----	-------------------	-----	------

**LIGHTS**

**28. NAVIGATION LIGHTS - WING**

A. Whelen Engineering Co.

1.	A650 PR (Red) (Power Supply A490-T-DF-14)	1.8	17.5
2.	A650 PG (Green) (Power Supply A490-T-DF-14)	1.8	17.5
3.	62-A470-W (Power Supply A490-T-DF-14)	.5	37.9
4.	A650 PR (Red) (Power Supply A490-T-DF-28) (28 V)	1.8	17.5
5.	A650 PG (Green) (Power Supply A490-T-DF-28) (28 V)	.8	17.5

B. See Optional Equipment List, Section 1.A, Items 1, 2 and 5.

**29. NAVIGATION LIGHTS - TAIL**

A. Grimes

1.	Type A-2064 (14 or 28 volt)	.2	199.0
----	-----------------------------	----	-------

B. Luminator Aircraft

1.	5107 C14B	.2	199.0
----	-----------	----	-------

**EMERGENCY LOCATION TRANSMITTERS (ELT)**

**30. ELT**

A. Leigh

1.	7H-2-190 Mod. # Type AF/AP/P	2.3	18.8
----	------------------------------	-----	------

B. Narco

1.	ELT-10	3.5	18.8
----	--------	-----	------

C. Emergency Beacon Corp.

1.	EBC-102A	1.2	36.7
2.	EBC-502	2.8	36.7

D. Merl, Inc.

1.	Model #79007-P	2.5	20.0
----	----------------	-----	------

E. ARTEX

1.	ME-406	3.3	MX7/105.8 &
2.	ME-406P	3.3	M7/104.5